MIC-713-ON

AI Platform Based on NVIDIA® Jetson Orin™ Nano



Features

- Compact fanless design
- Embedded NVIDIA® Jetson Orin™ Nano up to 67 TOPS
- Supports 2 x GbE, 6 x USB 3.2 Gen 2
- Supports 1 x mPCIe, 1 x M.2 3052, 1 x M.2 2280
- Supports AIIxon 24/7 remote monitoring and OTA deployment
- Supports Super mode with Jetpack 6.2 and above

Specifications


		NVIDIA® Jetson Orin™ Nano
Processor System	CPU	8GB: 6-core NVIDIA Arm Cortex A78AE v8.2 64-bit CPU 4GB: 6-core NVIDIA Arm Cortex A78AE v8.2 64-bit CPU
	GPU	8GB: 1024 core NVIDIA Ampere GPU with 32 Tensor Cores 4GB: 512 core NVIDIA Ampere GPU with 16 Tensor Cores
	Memory	8GB: 8GB LPDDR5 4GB: 4GB LPDDR5
	Flash	-
I/O	Ethernet*	2 x 10/100/1000 Mbps
	Display	HDMI (Max. resolution 3840x2160 @ 60Hz)
	USB	External: 6 x USB 3.2 Gen 2
	Digital I/O	4-ch DI, 4-ch DO
	Serial Port (Optional)	2 x RS-232/422/485 (On-board pin header reserved)
	CANBus	1 x CAN FD (5M)
	OTG USB	1 x Micro USB
Expansion	Mini PCIe	1 x mPCIe (Signal: PCIe + USB 2.0)
	M.2	1 x M.2 3052 (Signal: USB)
	SIM	2 x Nano SIM slots
	TPM (Optional)	1 x TPM 2.0
	GMSL (Optional)	1 x MIPI connector for GMSL video capture card
Storage	M.2	1 x M.2 2280 (Signal: PCIe x1, Gen 4)
	SD Card	1 x Micro SD
Power	Mode	AT
	Input Voltage	9 ~ 36 V_{DC}
Environment	Operating Temperature**	-10 ~ 60 °C with 0.7 m/s airflow (-10~50°C with MAXN_SUPER)
	Operating Humidity	95% @ 40 °C (non-condensing)
	Vibration	3 Grms @ 5 ~ 500 Hz, random, 1 hr/axis
	Shock	10G / 11ms
Mechanical	Dimensions (W x D x H)	194.8 x 174.3 x 65.85 mm (7.67" x 6.86" x 2.59")
	Weight	2.05 kg (w/o packing material)
	Installation	Desktop
BSP	Jetpack	Above 5.1
Certifications		CE/FCC/UKCA/CB/UL/BSMI/CCC (No RED certification)

* PoE function by request.
** Depending on the installation situation and interface connection. Derating of max. operating temp. is possible when using the cellular LTE module. Please see user documentation.

All product specifications are subject to change without notice.
Last updated: 11-Aug-2026

Dimensions

Unit: mm



Ordering Information

Part Number	NVIDIA Module	NVIDIA Module Memory	Installed Jetpack version	NVMe	Super mode support
MIC-713-ON3B2	Orin Nano	8GB	JP6.2	128GB pre installed	Yes
MIC-713-ON2B2	Orin Nano	4GB	JP6.2	128GB pre installed	Yes
MIC-713-ON3B3	Orin Nano	8GB	NA	NA	Yes
MIC-713-ON2B3	Orin Nano	4GB	NA	NA	Yes

Packing List

Part Number	Description	Quantity
MIC-713-ON	MIC-713 Fanless system	1
1652005204	DI/DO Terminal Block	2
1652003234	DC-In Terminal Block	1
1700023619-01	Micro USB cable for System recovery	1

Part Number	Description	Quantity
1930005673-11	Screw M3x4.5L for GMSL card	3
1960110505N001	Mounting Bracket	2
1930007259-01	Screw M4x4L for mounting bracket	4
193A230600	POST F=M3x5L M=M3x5L B=5 H=6.5 Cu for GMSL (only for Bx version)	3

Optional

Category	Part Number	Description	Quantity
Adapter	96PSA-A150W19P4-4	Power Adapter 100-240V 150W 19V C14	1
Power cord	1702002600	Power Cord UL 3P 15A 125V C13 183 cm (US)	1
	1702002605	Power Cord EU 3P 10A 250V C13 183cm (EU)	1
	1702031801	Power Cord BSI 3P 10A 250V C13 183cm (UK)	1
	1700020098	Power Cord SAA 3P 10A 250V C13 183cm (AU)	1
	1700029019-01	Power Cord (PSE/BSMI), 3-pin, 7A, 125V, 1.8 M	1
	1700000596-11	Power Cord CCC 3P 10A 250V C13 183cm (China)	1
TPM	PCA-TPMSPI-00A1	PCA-TPMSPI-00A1	1
Cable	1700019968	COM port cable (2 ports)	1
	1700027920-01	Audio port cable (1 x Line-In + 1 x Mic)	1
GMSL	MIC-FG-4G2C1	4ch GMSL Video Capture Card	1
	1751000805-01	RF Cable FAKRA-Z/F FAKRA-Z/F KS302 BLK L15M	by camera quantity
Wifi	EWM-W173H01E	Wi-Fi 6+BT 5.0 Module 2.4/5GHz Mini PCIe	1
	1751000626-01	RF Cable SMA/F-R MHF1/113 BLK L250mm	2
	1751000460-01	Dipole Ant. WiFi 6E SMA/M-R BLK L111.7mm IP54 (Wi-Fi)	2
5G	AIW-356-DQ	5G Sub6+GNSS M.2 3052 Key B (by region)	1
	1751000624-01	Cable Ant. SMA/F MHF4L/113 BLK L250mm (5G)	4
	1750009372-01	Ant.SMA/M 90/180 5G BLK 167mm RG178 (5G)	4
Bracket	1960065854N021	Bracket for idoor PCM series add-on module	1
	98R27130000	MIC-713 DIN rail kit	1
OOB	98RV710AL00	Allxon OOB module	1